



**SEMIPACK® 5**

## Thyristor / Diode Modules

**SKKT 460**

**SKKH 460**

### Features

- Heat transfer through aluminium nitride ceramic insulated metal baseplate
- Precious metal pressure contacts for high reliability
- UL recognized, file no. E63532

### Typical Applications


- AC motor softstarters
- Input converters for AC inverter drives
- DC motor control (e.g. for machine tools)
- Temperature control (e.g. for ovens , chemical, processes)
- Professionals light dimming (studios, theaters)

1) see assembly instructions

2) screws must be lubricated

$V_{RSM}$ V	$V_{RRM}, V_{DRM}$ V	$I_{TRMS} = 800 \text{ A}$ (maximum value for continuous operation) $I_{TAV} = 460 \text{ A}$ (sin. 180; $T_c = 85^\circ\text{C}$ )		
1700	1600	SKKT 460/16E	SKKH 460/16E	
2100	2000	SKKT 460/20E H4	SKKH 460/20E H4	
2300	2200	SKKT 460/22E H4	SKKH 460/22E H4	

Symbol	Conditions	Values	Units
$I_{TAV}$	sin. 180; $T_c = 85$ (100) $^\circ\text{C}$ ;	460 (335)	A
$I_{TSM}$	$T_{vj} = 25^\circ\text{C}; 10 \text{ ms}$ $T_{vj} = 130^\circ\text{C}; 10 \text{ ms}$	18000	A
$i^2t$	$T_{vj} = 25^\circ\text{C}; 8,3 \dots 10 \text{ ms}$ $T_{vj} = 130^\circ\text{C}; 8,3 \dots 10 \text{ ms}$	15500 1620000 1200000	A <sup>2</sup> s A <sup>2</sup> s
$V_T$	$T_{vj} = 25^\circ\text{C}; I_T = 1400 \text{ A}$	max. 1,6	V
$V_{T(TO)}$	$T_{vj} = 130^\circ\text{C}$	max. 0,88	V
$r_T$	$T_{vj} = 130^\circ\text{C}$	max. 0,45	mΩ
$I_{DD}; I_{RD}$	$T_{vj} = 130^\circ\text{C}; V_{RD} = V_{RRM}; V_{DD} = V_{DRM}$	max. 240	mA
$t_{gd}$	$T_{vj} = 25^\circ\text{C}; I_G = 1 \text{ A}; dI_G/dt = 1 \text{ A}/\mu\text{s}$	1	μs
$t_{gr}$	$V_D = 0,67 * V_{DRM}$	2	μs
$(di/dt)_{cr}$	$T_{vj} = 130^\circ\text{C}$	max. 250	A/μs
$(dv/dt)_{cr}$	$T_{vj} = 130^\circ\text{C}$	max. 1000	V/μs
$t_q$	$T_{vj} = 130^\circ\text{C}$ ,	100 .. 200	μs
$I_H$	$T_{vj} = 25^\circ\text{C}; \text{typ. / max.}$	150 / 500	mA
$I_L$	$T_{vj} = 25^\circ\text{C}; R_G = 33 \Omega; \text{typ. / max.}$	300 / 2000	mA
$V_{GT}$	$T_{vj} = 25^\circ\text{C}; \text{d.c.}$	min. 3	V
$I_{GT}$	$T_{vj} = 25^\circ\text{C}; \text{d.c.}$	min. 200	mA
$V_{GD}$	$T_{vj} = 130^\circ\text{C}; \text{d.c.}$	max. 0,25	V
$I_{GD}$	$T_{vj} = 130^\circ\text{C}; \text{d.c.}$	max. 10	mA
$R_{th(j-c)}$	cont.; per thyristor / per module	0,072 / 0,035	K/W
$R_{th(j-c)}$	sin. 180°; per thyristor / per module	0,074 / 0,037	K/W
$R_{th(j-c)}$	rec. 120°; per thyristor / per module	0,078 / 0,039	K/W
$R_{th(c-s)}$	per thyristor / per module	0,02 / 0,01	K/W
$T_{vj}$		- 40 ... + 130	°C
$T_{stg}$		- 40 ... + 125	°C
$V_{isol}$	a.c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
$V_{isol}$	a.c. 50 Hz; r.m.s.; 1 s / 1 min. for SKK...H4	4800 / 4000	V~
$M_s$	to heatsink	5 ± 15% <sup>1)</sup>	Nm
$M_t$	to terminals	12 ± 15% <sup>2)</sup>	Nm
$a$	approx.	5 * 9,81	m/s <sup>2</sup>
$m$		1400	g
Case	SKKT SKKH	A 60b A 66b	



SKKT

SKKH




Fig. 1I Power dissipation per thyristor vs. on-state current




Fig. 1r Power dissipation per thyristor vs. ambient temperature




Fig. 2I Power dissipation per module vs. rms current




Fig. 2R Power dissipation per module vs. case temp.




Fig. 3L Power dissipation of two modules vs. direct current











Fig. 3R Power dissipation of two modules vs. case temp.





This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.