

2SC0108T2Dx-12 Preliminary Data Sheet

Dual Channel Ultra-compact Low-cost SCALE-2 Driver Core

Short Description

The low-cost SCALE-2 dual-driver core 2SC0108T2Dx-12 combines unrivalled compactness with broad applicability. The driver is designed for universal applications requiring high reliability. The 2SC0108T2Dx-12 drives all usual IGBT modules up to 1200V. The embedded paralleling capability allows easy inverter design covering higher power ratings. Multi-level topologies are also supported.

The 2SC0108T2Dx-12 is the most compact driver core available for industrial applications, with a footprint of only 45 x 34.3mm and an insertion height of max. 16mm. It allows even the most restricted insertion spaces to be efficiently used. Compared with conventional drivers, the highly integrated SCALE-2 chipset allows about 85% of components to be dispensed with. This advantage is impressively reflected in increased reliability at simultaneously minimized cost.

The 2SC0108T2Dx-12 combines a complete two-channel driver core with all components required for driving, such as an isolated DC/DC converter, short-circuit protection, advanced active clamping as well as supply voltage monitoring. Each of the two output channels is electrically isolated from the primary side and the other secondary channel.

An output current of 8A and 1W drive power is available per channel, making the 2SC0108T2Dx-12 an ideal driver platform for universal usage in small and medium power applications. The driver provides a gate voltage swing of +15V/-8V. The turn-on voltage is regulated to maintain a stable 15V regardless of the output power level.

Its outstanding EMC allows safe and reliable operation in even hard industrial applications.

Product Highlights

Applications

- | | |
|---|--|
| <ul style="list-style-type: none">✓ Ultra-compact dual channel driver✓ Highly integrated SCALE-2 chipset✓ Gate current $\pm 8A$, 1W output power per channel✓ +15V/-8V gate driving✓ Blocking voltages up to 1200V✓ Safe isolation to EN 50178✓ Short delay and low jitter✓ Interface for 3.3V...15V logic level✓ UL compliant | <ul style="list-style-type: none">✓ General purpose drives✓ Uninterruptible power supplies (UPS)✓ Solar and wind power converters✓ Auxiliary converters for traction✓ Electro/hybrid drive vehicles✓ Driving parallel-connected IGBTs✓ Switched mode power supplies (SMPS)✓ Medical (MRT, CT, X-Ray)✓ Laser technology |
|---|--|

Preliminary Data Sheet

Safety Notice!

The data contained in this data sheet is intended exclusively for technically trained staff. Handling all high-voltage equipment involves risk to life. Strict compliance with the respective safety regulations is mandatory!

Any handling of electronic devices is subject to the general specifications for protecting electrostatic-sensitive devices according to international standard IEC 60747-1, Chapter IX or European standard EN 100015 (i.e. the workplace, tools, etc. must comply with these standards). Otherwise, this product may be damaged.

Important Product Documentation

This data sheet contains only product-specific data. For a detailed description, must-read application notes and important information that apply to this product, please refer to "2SC0108T2Dx-xx Description & Application Manual" on www.IGBT-Driver.com/go/2SC0108T

Absolute Maximum Ratings

Parameter	Remarks	Min	Max	Unit
Supply voltage V _{CC}	VCC to GND	0	16	V
Logic input and output voltages	Primary side, to GND	-0.5	VCC+0.5	V
SO _x current	Failure condition, total current	20		mA
Gate peak current I _{out}	Note 1	-8	+8	A
External gate resistance	Turn-on and turn-off	2		Ω
IGBT gate charge		6.3		µC
Average supply current I _{cc}	Notes 2, 3	260		mA
Output power	Ambient temperature <70°C (Notes 4, 5)	1.2		W
	Ambient temperature <85°C (Note 4)	1		W
Test voltage (50Hz/1min.)	Primary to secondary (Note 14)	3800		V _{AC(eff)}
	Secondary to secondary (Note 14)	3800		V _{AC(eff)}
Switching frequency F		50		kHz
dV/dt	Rate of change of input to output voltage (Note 10)	50		kV/µs
Operating voltage	Primary/secondary, secondary/secondary	1200		V _{peak}
Operating temperature	Note 5	-40	+85	°C
Storage temperature		-40	+90	°C

Recommended Operating Conditions

Power Supply	Remarks	Min	Typ	Max	Unit
Supply voltage V _{CC}	VCC to GND	14.5	15	15.5	V

Preliminary Data Sheet

Electrical Characteristics

All data refer to $+25^{\circ}\text{C}$ and $V_{\text{CC}} = 15\text{V}$ unless otherwise specified.

Power supply	Remarks	Min	Typ	Max	Unit
Supply current I_{CC}	Without load	31			mA
Coupling capacitance C_{io}	Primary side to secondary side, per channel	23			pF
Power Supply Monitoring	Remarks	Min	Typ	Max	Unit
Supply threshold V_{CC}	Primary side, clear fault	11.9	12.6	13.3	V
	Primary side, set fault (Note 11)	11.3	12.0	12.7	V
Monitoring hysteresis	Primary side, set/clear fault	0.35			V
Supply threshold $V_{\text{ISOx}} - V_{\text{Ex}}$	Secondary side, clear fault	12.1	12.6	13.1	V
	Secondary side, set fault (Note 12)	11.5	12.0	12.5	V
Monitoring hysteresis	Secondary side, set/clear fault	0.35			V
Supply threshold $V_{\text{Ex}} - V_{\text{COMx}}$	Secondary side, clear fault	5	5.15	5.3	V
	Secondary side, set fault (Note 12)	4.7	4.85	5	V
Monitoring hysteresis	Secondary side, set/clear fault	0.15			V
Logic Inputs and Outputs	Remarks	Min	Typ	Max	Unit
Input bias current	$V(\text{INx}) > 3\text{V}$	190			μA
Turn-on threshold	$V(\text{INx})$	2.6			V
Turn-off threshold	$V(\text{INx})$	1.3			V
SOx output voltage	Failure condition, $I(\text{SOx}) < 20\text{mA}$			0.7	V
Short-Circuit Protection	Remarks	Min	Typ	Max	Unit
Vce-monitoring threshold	Note 18	9.3			V
Minimum response time	Note 8	1			μs
Minimum blocking time	Note 9	9			μs
Timing Characteristics	Remarks	Min	Typ	Max	Unit
Turn-on delay $t_{d(\text{on})}$	Note 6	90			ns
Turn-off delay $t_{d(\text{off})}$	Note 6	75			ns
Jitter of turn-on delay	Note 17	± 2			ns
Jitter of turn-off delay	Note 17	± 2			ns
Output rise time $t_{r(\text{out})}$	Note 7	17			ns
Output fall time $t_{f(\text{out})}$	Note 7	15			ns
Transmission delay of fault state	Note 13	360			ns

Preliminary Data Sheet

Electrical Isolation	Remarks	Min	Typ	Max	Unit
Test voltage (50Hz/1s)	Primary to secondary side (Note 14) Secondary to secondary side (Note 14)	3800 3800	3850 3850	3900 3900	V _{eff} V _{eff}
Partial discharge extinction volt.	Primary to secondary side (Note 16) Secondary to secondary side (Note 16)	1220 1200			V _{peak} V _{peak}
Creepage distance	Primary to secondary side Secondary to secondary side	12.9 8.5			mm mm
Clearance distance	Primary to secondary side Secondary to secondary side	12.9 6.0			mm mm
Outputs	Remarks	Min	Typ	Max	Unit
Blocking capacitance	VISOx to VEx VEx to COMx		9.4 9.4		μF μF
Internal gate resistance	Turn-on and turn-off (Note 15)		0.5		Ω

Output voltage swing

The output voltage swing consists of two distinct segments. First, there is the turn-on voltage V_{GHx} between pins GHx and VEx. V_{GHx} is regulated and maintained at a constant level for all output power values and frequencies.

The second segment of the output voltage swing is the turn-off voltage V_{GLx} . V_{GLx} is measured between pins GLx and VEx. It is a negative voltage. It changes with the output power to accommodate the inevitable voltage drop across the internal DC/DC converter.

Output Voltage	Remarks	Min	Typ	Max	Unit
Turn-on voltage, V_{GHx}	Any load condition		15.0		V
Turn-off voltage, V_{GLx}	No load		-9.4		V
Turn-off voltage, V_{GLx}	1W output power		-7.6		V
Turn-off voltage, V_{GLx}	1.2W output power		-7.2		V

Footnotes to the Key Data

- 1) The maximum peak gate current refers to the highest current level occurring during the product lifetime. It is an absolute value and does also apply for short pulses.
- 2) The average supply input current is limited for thermal reasons. Higher values than specified by the absolute maximum rating are permissible (e.g. during power supply start up) if the average remains below the given value, provided the average is taken over a time period which is shorter than the thermal time constants of the driver in the application.
- 3) There is no means of actively controlling or limiting the input current in the driver. In the case of start-up with very high blocking capacitor values, or in case of short circuit at the output, the supply input current has to be limited externally.
- 4) The maximum output power must not be exceeded at any time during operation. The absolute maximum rating must also be observed for time periods shorter than the thermal time constants of the driver in the application.

Preliminary Data Sheet

- 5) An extended output power range is specified in the output power section for maximum ambient temperatures of 70°C. In that case, the absolute maximum rating for the operating temperature changes to (-40°C - 70°C) and the absolute maximum output power rating changes to 1.2W.
- 6) The delay time is measured between 50% of the input signal and 10% voltage swing of the corresponding output. The delay time is independent of the output loading.
- 7) Output rise and fall times are measured between 10% and 90% of the nominal output swing. The values are given for the driver side of the gate resistors without load. The time constant of the output load in conjunction with the present gate resistors leads to an additional delay at the load side of the gate resistors.
- 8) The minimum response time given is valid for the circuit given in the description and application manual (Fig. 6) with the values of table 1 ($C_{ax}=0\text{pF}$).
- 9) The blocking time sets a minimum time span between the end of any fault state and the start of normal operation (remove fault from pin SO_x). The value of the blocking time can be adjusted at pin TB. The specified blocking time is valid if TB is connected to GND.
- 10) This specification guarantees that the drive information will be transferred reliably even at a high DC-link voltage and with ultra-fast switching operations.
- 11) Undervoltage monitoring of the primary-side supply voltage (VCC to GND). If the voltage drops below this limit, a fault is transmitted to both SO_x outputs and the IGBTs are switched off.
- 12) Undervoltage monitoring of the secondary-side supply voltage (VISO_x to VEx and VEx to COM_x which correspond with the approximate turn-on and turn-off gate-emitter voltages). If the corresponding voltage drops below this limit, the IGBT is switched off and a fault is transmitted to the corresponding SO_x output.
- 13) Transmission delay of fault state from the secondary side to the corresponding primary status output.
- 14) HiPot testing (= dielectric testing) must generally be restricted to suitable components. This gate driver is suited for HiPot testing. Nevertheless, it is strongly recommended to limit the testing time to 1s slots as stipulated by EN 50178. Excessive HiPot testing at voltages much higher than $850\text{V}_{AC(eff)}$ may lead to insulation degradation. No degradation has been observed over 1min. testing at $3800\text{V}_{AC(eff)}$. Every production sample shipped to customers has undergone 100% testing at the given value or higher (<math><5100\text{V}_{eff}</math>) for 1s.
- 15) The resulting gate resistance is the sum of the external and the internal gate resistance.
- 16) Partial discharge measurement is performed in accordance with IEC 60270 and isolation coordination specified in EN 50178. The partial discharge extinction voltage between primary and either secondary side is coordinated for safe isolation to EN 50178.
- 17) Jitter measurements are performed with input signals IN_x switching between 0V and 5V referred to GND, with a corresponding rise time and fall time of 15ns
- 18) The Vce-monitoring threshold cannot be modified by the user.

Legal Disclaimer

This data sheet specifies devices but cannot promise to deliver any specific characteristics. No warranty or guarantee is given – either expressly or implicitly – regarding delivery, performance or suitability.

CT-Concept Technologie AG reserves the right to make modifications to its technical data and product specifications at any time without prior notice. The general terms and conditions of delivery of CT-Concept Technologie AG apply.

Preliminary Data Sheet

Ordering Information

The general terms and conditions of delivery of CT-Concept Technologie AG apply.

Type Designation	Description
2SC0108T2D0-12	Dual-channel SCALE-2 driver core

Product home page: www.IGBT-Driver.com/go/2SC0108T

Refer to www.IGBT-Driver.com/go/nomenclature for information on driver nomenclature

Information about Other Products

For other drivers, product documentation, and application support

Please click: www.IGBT-Driver.com

Manufacturer

CT-Concept Technologie AG
Intelligent Power Electronics
Renferstrasse 15
CH-2504 Biel-Bienne
Switzerland

Tel. +41 - 32 - 344 47 47
Fax +41 - 32 - 344 47 40

E-mail Info@IGBT-Driver.com
Internet www.IGBT-Driver.com

© 2011...2012 CT-Concept Technologie AG - Switzerland.
We reserve the right to make any technical modifications without prior notice.

All rights reserved.
Version from 2012-05-03